

Hollow drill bit SB



Description

The hollow drill bit SB combines two steps in one: it drills and at the same time removes the drilling dust from the hole. As a result, it significantly reduces the dust created, resulting in a cleaner work space and reduces air contamination. Contamination in the work area is also avoided, making it the ideal hammer drill for indoors. Many MKT injection systems eliminate the need for additional cleaning, increasing efficiency and installation safety. Thanks to its SDS shank and its 38mm suction pipe connection, it can be used universally and flexibly with any SDS hammer drill and industrial vacuum cleaners.

Advantages

- 98% less air borne dust than during conventional drilling processes
- Permitted for use with approved anchors
- The separate cleaning of the drill hole can be omitted if this is permitted in the ETA
- Easy handling, insert in a hammer drill and connect to an industrial vacuum cleaner
- Efficient dust extraction and drilling thanks to extra large vacuum holes
- Optimum health and safety at the workplace, reduce respiratory complaints of dust particles by using an industrial vacuum cleaner of the M-Class
- Save money and time: there is no dirt generated, so no need to clean up afterwards
- Can be used with all standard SDS-max and SDS-plus hammer drills in conjunction with commercial industrial vacuum cleaners

Applications

For dust-free drilling in concrete, solid brick, solid lime and stone and natural stone indoors and outdoors.

Hollow drill bit with SDS-plus shank

→ 2-cutter with big vacuum holes for a fast drilling

Description	Ref.No.	Ø mm	Drilling depth mm	Total length mm	Adaptor	Type	Pkg. Content pcs.	Weight per pcs. kg
Hollow drill bit SB plus 8x270	50235501	8	150	270	SDS-plus	2-cutter	1	0,21
Hollow drill bit SB plus 10x270	50245501	10	150	270	SDS-plus	2-cutter	1	0,24
Hollow drill bit SB plus 12x320	50256001	12	200	320	SDS-plus	2-cutter	1	0,31
Hollow drill bit SB plus 14x370	50266501	14	250	370	SDS-plus	2-cutter	1	0,39
Hollow drill bit SB plus 16x370	50286501	16	250	370	SDS-plus	2-cutter	1	0,43
Hollow drill bit SB plus 18x370	50296501	18	250	370	SDS-plus	2-cutter	1	0,53
Hollow drill bit SB plus 20x370	50306501	20	250	370	SDS-plus	2-cutter	1	0,64
Hollow drill bit SB plus 24x370	50326501	24	250	370	SDS-plus	2-cutter	1	0,81

Hollow drill bit with SDS-max shank

→ Y-Cutter for more stable drilling

Description	Ref.No.	Ø mm	Drilling depth mm	Total length mm	Adaptor	Type	Pkg. Content pcs.	Weight per pcs. kg
Hollow drill bit SB max 18x600	50698001	18	400	600	SDS-max	Y-cutter	1	0,99
Hollow drill bit SB max 24x600	50728001	24	400	600	SDS-max	Y-cutter	1	1,21
Hollow drill bit SB max 25x600	50738001	25	400	600	SDS-max	Y-cutter	1	1,23

Suction bell ASG



Description	Ref.No.	Connection diameter to a vacuum cleaner Ø [mm]	Suitable for drill hole Ø [mm]	Pkg. Content pcs.	Weight per pc. kg
Suction bell ASG	29980001	30-38	6-32	1	0,06

Description

For removing drilling dust when drilling or cleaning holes.

Advantages

- Easy handling, connection to a vacuum cleaner is sufficient
- No mounting is necessary, because the suction bell sticks tight to floor, wall and ceiling by a strong vacuum
- Prevents contamination and provides a clear visibility due to almost dust-free drilling
- Reduce respiratory complaints due to tiny dust particles by using a vacuum cleaner of the M-Class